

EAD

EN 1492: 1 / S.F. 7:1

Eslinga abierta 2 capas
Two-layer flat slings. Élingues plates 2 épaisseur



EAD 1000

ANCHO / WIDTH / LARGEUR (mm): 30

		CMU / SWL (kg)
	x 1	1.000
	x 0,8	800
	x 2	2.000
	x 1,4 (x = 0° ÷ 45°)	1.400

EAD 1500

ANCHO / WIDTH / LARGEUR (mm): 50

		CMU / SWL (kg)
	x 1	1.500
	x 0,8	1.200
	x 2	3.000
	x 1,4 (x = 0° ÷ 45°)	2.100

EAD 2000

ANCHO / WIDTH / LARGEUR (mm): 60

		CMU / SWL (kg)
	x 1	2.000
	x 0,8	1.600
	x 2	4.000
	x 1,4 (x = 0° ÷ 45°)	2.800

EAD 3000

ANCHO / WIDTH / LARGEUR (mm): 90

		CMU / SWL (kg)
	x 1	3.000
	x 0,8	2.400
	x 2	6.000
	x 1,4 (x = 0° ÷ 45°)	4.200

EAD 4000

ANCHO / WIDTH / LARGEUR (mm): 120

		CMU / SWL (kg)
	x 1	4.000
	x 0,8	3.200
	x 2	8.000
	x 1,4 (x = 0° ÷ 45°)	5.600

EAD 5000

ANCHO / WIDTH / LARGEUR (mm): 150

		CMU / SWL (kg)
	x 1	5.000
	x 0,8	4.000
	x 2	10.000
	x 1,4 (x = 0° ÷ 45°)	7.000

EAD 6000

ANCHO / WIDTH / LARGEUR (mm): 180

		CMU / SWL (kg)
	x 1	6.000
	x 0,8	4.800
	x 2	12.000
	x 1,4 (x = 0° ÷ 45°)	8.400

EAD 8000

ANCHO / WIDTH / LARGEUR (mm): 240

		CMU / SWL (kg)
	x 1	8.000
	x 0,8	6.400
	x 2	16.000
	x 1,4 (x = 0° ÷ 45°)	11.200

EAD 10000

ANCHO / WIDTH / LARGEUR (mm): 300

		CMU / SWL (kg)
	x 1	10.000
	x 0,8	8.000
	x 2	20.000
	x 1,4 (x = 0° ÷ 45°)	14.000

EAD 12000

ANCHO / WIDTH / LARGEUR (mm): 300

		CMU / SWL (kg)
	x 1	12.000
	x 0,8	9.600
	x 2	24.000
	x 1,4 (x = 0° ÷ 45°)	16.800